


6X12 FC Wire Rope



6x12 FC

Rope Diameter (mm)	Minimum Breaking load in Metric Tons	
	Galvanised 150Kg/mm2	Approx. Weight (Kg/m)
3	0.3	0.025
4	0.53	0.044
5	0.83	0.068
6	1.2	0.098
6.3	1.32	0.108
8	2.13	0.175
9	2.7	0.221
10	3.33	0.273
11.2	4.18	0.343
12	4.8	0.393
12.5	5.2	0.427
14	6.53	0.535
16	8.52	0.699
18	10.8	0.885
20	13.3	1.09
22	16.1	1.32
22.4	16.7	1.37
24	19.2	1.57
25	20.8	1.71
26	22.5	1.85
28	26.1	2.14
30	30	2.46
31.5	33	2.71
32	34.1	2.8
33.5	37.4	3.06
35.5	42	3.44
36	43.2	3.54
37.5	46.8	3.84
40	53.3	4.37
42.5	60.2	4.93
45	67.5	5.53
47.5	75.2	6.16
50	83.3	6.83
53	93.6	7.67
56	104.5	8.57
60	119.9	9.83
63	132.2	10.84
70	163.2	13.4
75	187.4	15.4

(Remark: All Weights & Dimensions are approximate, the measurements may vary between different factories)

