


## 6X24 FC Wire Rope



6x24 FC

Rope Diameter (mm)	Minimum Breaking load in Metric Tons		Approx. Weight (Kg/m)
	Galvanised 150Kg/mm2	Galv'd & Ungalv'd 165Kg/mm2	
4	0.74	0.8	0.053
5	1.16	1.25	0.083
6.3	1.84	1.99	0.131
8	2.97	3.21	0.212
9	3.75	4.06	0.269
10	4.64	5.02	0.332
11.5	5.82	6.29	0.416
12	6.68	7.22	0.478
12.5	7.25	7.84	0.519
14	9.09	9.83	0.651
16	11.9	12.8	0.85
18	15	16.2	1.08
20	18.5	20.1	1.33
22.4	23.3	25.2	1.67
24	26.7	28.9	1.91
25	29	31.3	2.08
26	31.4	33.9	2.24
28	36.4	39.3	2.6
30	41.8	45.1	2.99
31.5	46	49.8	3.29
32	47.5	51.4	3.4
33.5	52.1	56.3	3.73
35.5	58.5	63.2	4.18
37.5	65.2	70.5	4.67
40	74.2	80.2	5.31
42.5	83.8	90.6	6
45	94	102	6.72
47.5	105	113	7.49
50	117	125	8.3
53	130	141	9.33
56	145	157	10.4
60	167	180	12
63	184	199	13.2
76	267	290	19.2
85	335	363	24
90	376	407	27

(Remark: All Weights & Dimensions are approximate, the measurements may vary between different factories)

