

Specifications of Synthetic Ropes

These products are manufactured in several international standards according to the destinations where the goods will be consumed. The major standards are Korean Standards, Japanese Industrial Standards, US Standards and British Standards.

Items	Specifications	Use
Polypropylene Rope (Monofilament)	a.) 3 strand, Z-twisted, 200 or 220 meters per coil Dia. (size) 3mm to 100mm, Assorted color. b.) 8-strand plated, 200 or 220 meters per coil Dia. (size) 40mm to 100mm, Assorted color.	1. For vessels, Fisheries, Sea culture 2. Guideline, Packing etc.
Nylon Rope (Multifilament)	a.) 3 strand, Z-twisted, 200 or 220 meters per coil Dia. (size) 4mm to 100mm, White color only. b.) 8-strand plated, 200 or 220 meters per coil Dia. (size) 40mm to 100mm, White color only.	1. For vessels, Fisheries, Whaleline, Mooring Lines etc. 2. For Ship's mooring
Polypropylene Rope (Multifilament)	a.) 3 strand, Z-twisted, 200 or 220 meters per coil Dia. (size) 4mm to 100mm, White color only. b.) 8-strand plated, 200 or 220 meters per coil Dia. (size) 40mm to 100mm, White color only.	1. For vessels, Fisheries, Whaleline, Mooring Lines etc. 2. For Ship's mooring
Manila and Sisal Rope	a.) 3 strand, Z-twisted, 200 or 220 meters per coil Dia. (size) 4mm to 80mm	1. For vessels, Fisheries, Sea culture