




Wire Rope




6x19S+FC



6x19S+IWRC



6x19W+FC



6x19W+IWRC

Used In Crane, Lifting, Hauling, Hoist, Drilling

Nominal Diameter		Approximate Weight		Nominal Tensile Strength (N/mm ²)							
				1570		1670		1770		1870	
mm	Inch	kg/100m		Min. Breaking Strength (KN)							
		FC	IWRC	FC	IWRC	FC	IWRC	FC	IWRC	FC	IWRC
8	5/16	23.6	25.9	33.4	35.7	35.2	38	37.3	40.3	39.4	42.6
9	3/8	29.9	32.8	41.9	45.2	44.6	48.1	47.3	51	49.9	53.9
10	13/32	36.9	40.5	51.8	55.8	55.1	59.4	58.4	63	61.7	66.5
11	7/16	44.6	49.1	62.6	67.6	66.6	71.9	70.6	76.2	74.6	80.5
12	1/2	53.1	58.4	74.6	80.4	79.3	85.6	84.1	90.7	88.8	95.8
13	1/2	62.3	68.5	87.5	94.4	93.1	100	98.7	106	104	112
14	9/16	72.2	79.5	101	109	108	116	114	123	120	130
16	5/8	94.4	104	132	143	141	152	149	161	157	170
18	11/16	119	131	167	181	178	192	189	204	199	215
20	13/16	147	162	207	223	220	237	233	252	246	266
22	7/8	178	196	250	270	266	287	282	304	298	322
24	15/16	212	234	298	321	317	342	336	362	355	383
26	1	249	274	350	377	372	401	394	425	417	450
28	1-1/8	289	318	406	438	432	466	457	494	483	521
30	1-3/16	322	365	466	503	495	535	525	567	555	599
32	1-1/4	377	415	530	572	564	608	598	645	631	681
34	--	426	469	598	646	637	687	675	728	713	769
36	--	478	525	671	724	714	770	756	816	799	862

(Remark: All Weights & Dimensions are approximate, the measurements may vary between different factories)

