



Wire Rope




6x29Fi+FC



6x29Fi+IWRC



631WS+FC



6x31WS+IWRC

Used In Crane, Lifting, Hauling, Cableway, Power Shovel

Nominal Diameter		Approximate Weight		Nominal Tensile Strength (N/mm ²)					
				1670		1770		1870	
mm	Inch	kg/100m		Min. Breaking Strength (KN)					
		FC	IWRC	FC	IWRC	FC	IWRC	FC	IWRC
10	13/32	39.1	43.2	56.9	61.9	60.3	66.5	63.7	69.4
12	1/2	56	62.2	81.9	89.3	86.8	95.2	91.7	99.9
14	9/16	75.8	82.5	109	119	116	126	123	133
16	5/8	98.5	109.5	142	155	150	165	158	173
18	11/16	125	137	179	195	190	207	200	219
20	13/16	155	170	222	239	235	254	248	268
22	7/8	190	215	269	291	285	308	301	325
24	15/16	226	250	319	344	338	365	357	386
26	1	263	292	371	400	393	424	415	4487
28	1-1/8	305	338	430	464	456	492	480	518
32	1-1/4	351	401	493	533	523	565	550	593
34	--	402	438	561	607	595	642	625	675
36	1-2/5	500	546	709	766	752	812	793	855
38	1-1/2	570	630	794	858	842	908	888	958
40	1-19/32	620	680	880	951	933	1000	983	1060

(Remark: All Weights & Dimensions are approximate, the measurements may vary between different factories)

