


Wire Rope




6x36WS+FC



6x36WS+IWRC



6x37S+FC



6x37S+IWRC

Used in Hoist, Lifting, Crane, Heavy Machinery

Nominal Diameter		Approximate Weight		Nominal Tensile Strength (N/mm ²)					
				1670		1770		1870	
mm	Inch	kg/100m		Min. Breaking Strength (KN)					
		FC	IWRC	FC	IWRC	FC	IWRC	FC	IWRC
12	1/2	55.7	60.7	79.2	85.6	84	90.7	88.7	95.8
13	1/2	65.7	71.4	92.7	100	98.3	106	104	112
14	9/16	75.8	82.6	108	116	114	123	120	129
16	5/8	98.3	107.1	141	152	149	161	157	170
18	11/16	125	136.3	178	192	189	204	199	216
20	13/16	156	170.1	221	239	234	253	247	267
22	7/8	185	201.7	266	288	282	305	298	322
24	15/16	220	239.8	317	342	336	363	355	384
26	1	257	280.1	373	403	395	427	417	451
28	1-1/8	299	325.9	432	467	458	495	483	521
32	1-1/4	390	425.1	564	609	598	646	630	680
36	1-2/5	495	539.6	714	772	757	818	798	860
40	1-2/5	610	664.9	881	951	934	1008	985	1060
44	1-7/10	738	804.4	1066	1151	1130	1220	1190	1280
48	1-9/10	873	954.8	1274	1373	1350	1455	1420	1530

(Remark: All Weights & Dimensions are approximate, the measurements may vary between different factories)