



Wire Rope



4Vx39S+5FC



4Vx48S+5FC

Used for Port Loading Unloading & Tower Crane for Building

Nominal Diameter (mm)	Approximate Weight (kg/100m)	Nominal Tensile Strength (N/mm ²)				
		1470	1570	1670	1770	1870
		Min. Breaking Strength (KN)				
8	25.7	33.8	36.1	38.4	40.7	43
9	32.6	42.8	45.7	48.6	51.6	54.5
10	40.2	52.9	56.5	60.1	63.7	67.3
11	48.6	64	68.3	72.7	77.1	81.4
12	57.9	76.2	81.3	86.5	91.7	96.9
13	67.9	89.4	95.5	101	107	113
14	78.8	103	110	117	124	131
16	103	135	144	153	163	172
18	130	171	183	194	206	218
20	161	211	226	240	254	269
22	195	256	273	290	308	325
24	232	304	325	346	367	387
26	272	357	382	406	430	455
28	315	414	443	471	499	527
30	362	476	508	541	573	605
32	412	541	578	615	652	689
34	465	611	653	694	736	778
36	521	685	732	779	825	872
38	580	764	816	868	920	972
40	643	846	904	961	1018	1075
42	709	932.5	996.2	1059.6	1123.1	1186
44	778	1023.7	1093.3	1163	1232.6	1302.2
46	851	1118.9	1195	1271.1	1347.2	1423.3
48	926	1218.3	1301.1	1384	1466.9	1549.8
50	1005	1321.9	1400.8	1501.8	1591.7	1681.6

(Remark: All Weights & Dimensions are approximate, the measurements may vary between different factories)

